

The technical drawing illustrates a wheel assembly in two views: a side view on the left and a top view on the right.

- Side View (Left):** Shows the internal components of the wheel hub. Key parts include:
  - 706117:** Spannhülse (roll pin) 4x26-A EN ISO 8752 GEOMET Mechanical zinc plating as option.
  - 706118:** Spannhülse (roll pin) 6x26-A EN ISO 8752 GEOMET Mechanical zinc plating as option.
  - 2011730215:** A component at the top of the hub assembly.
  - 700767:** A component below 2011730215.
  - 365599:** A component further down the hub.
  - 374299:** A component at the bottom of the hub.
  - 692139:** A component at the very bottom of the hub.
  - A dimension of **ca. 110** is indicated for the overall height of the hub assembly.
  - A dimension of **20** is indicated for a specific part of the hub.
- Top View (Right):** Shows the wheel from above. Key features include:
  - Wheel Rim:** Labeled with **PVC-U**, **691604**, and **AL-KO 230 X 80**.
  - Hub Assembly:** The central part where the wheel meets the axle, showing various bolts and components.
  - Verklebung e Rad darf sich nicht drehen:** A note indicating that the wheel must not rotate after gluing.
  - Deadlock requires wheel not rotating:** An English translation of the German note.
  - X:** A coordinate axis pointing upwards.

Ident-Nr, Herstellerzeichen,  
Fertigungsdatum eingepreßt  
Ident-Nr, manufacturer's mark,  
date of production stamped

Ident-Nr, Herstellerzeichen,  
Fertigungsdatum eingepreßt  
Ident-Nr, manufacturer's mark,  
date of production stamped

706628  
Splint 5x50 DIN 94 ZN8DISP  
cotter 5x50 DIN 94 ZN8DISP

691604

692442

692441  
2x Splint 4x22 DIN 94 ZN8DISP  
2x cotter 4x22 DIN 94 ZN8DISP

705496  
2x Scheibe 14x20x1,5 DIN 988 ZN8DISP  
2x Washer 14x20x1,5 DIN 988 ZN8DISP

690444

702165  
704761  
Attention by assembly the second  
spring-type straight pin (704761)  
The slot's must be twisted against

692137

690450

690443

130

5 ±1

10 ±0,5

Mindenhöhe im Betriebszustand bei Raster 1: 315 ±10  
minimum height in workin order at lattice 1: 315 ±10

Mindenhöhe im Betriebszustand bei Raster 2: 365 ±10  
minimum height in working order at lattice 2: 365 ±10

Verstellbereich: 580 mm  
1. Klapphub 240 mm  
2. Verstellhub 340 mm

Adjustable range: 580 mm  
1. Turn down way: 240 mm  
2. Adjustable stroke: 340 mm

!! check the jockey wheel regarding currently!!

These following parts have to be greased:

- the guide slot and starting up place from the bolt 690450
- the bolt 690443 between inner tube and supporting shoe
- the thread on spindle 692139
- the thread nut from the innertube 692137

Außen- und Innenrohr feuerverzinkt;  
Stützschuh und Kleinteile:  
Galvanisch verzinkt, Cr6-frei;  
siehe Detailzeichnungen

External- and internal tube hot galvanized;  
support shoe and small parts:  
galvanic-zinc passivation, free of Cr6  
according of detail-drawings

Technical drawing of the 690770 adhesive label, showing side and front views with dimensions.

**Side View Dimensions:**

- Overall length: 294
- Length of main body: 120 ± 5
- Label part: 690770 Aufkleber Adhesive label

**Front View Dimensions:**

- Overall width: 70
- Top mounting holes: Raster 2: 50, Raster 1: 50, lattice 2: 50, lattice 1: 50
- Central slot width: 45
- Slot depth: 5
- Bottom mounting holes: 5, 11, 45
- Bottom hole diameter:  $\varnothing 11$

(587)